

550™ Bagging System

High Speed Bagging and Printing System

Bagging that optimizes flexibility for ecommerce order fulfillment, short-run, and build-on-demand operations



Markets Served



Mail Order and e-commerce Fulfillment



Prescription-by-mail Fulfillment



Catalog Order Fulfillment



Spare Parts Distribution



Any short-run production with frequent changeovers



37.1 to 47.1 in.

64.5 in. Length x 37.6 in. (Adjustable) Width

FEATURES AND BENEFITS

- Capable of cycling at speeds up to 45 bags per minute
- Next-bag-out printing prevents product queuing and reduces waste
- Efficient for applications that require frequent product and label changeovers
- Inherently safe, configurable for left- or right-hand access, and can be networked to facilitate full pack station integration and central monitoring
- Compact footprint minimizes floor space
- Dedicated service access simplifies maintenance and repairs to maximize uptime
- System-matched AUTOBAG brand pre-opened bags, AutoLabel Thermal Transfer Ribbon, and Autolabel Design Software
- Custom engineering & integration
- Can also be networked to facilitate full pack station integration and central monitoring

Technical Information

WEIGHT

390 lbs.

ELECTRICAL

Universal Input:
110V to 240V VAC, 50/60 Hz.
Power Consumption:
600W (VA) max

AIR FEED

5 CFM/80 psi of clean, dry air

PASS-THROUGH

5 in. max

BAG THICKNESS

1.09 – 4.0 mil

BAG SIZES

W 2 to 12 in. L 5 to 20 in.
(36 in. L unsupported)

WEIGHT CAPACITY

Up to 5 lbs. (with load shelf)