

## DESCRIPTION

The CRYOVAC® brand AutoVac 95 Vacuum Chamber System offers vacuum packaging flexibility for a broad variety of high-profile cuts of fresh red meat, processed meats, poultry and cheese. The single chamber system accommodates products of various shapes and sizes and the integrated buffer conveyor enables smooth machine feeding and minimizes the total footprint. This system is ideal for small and intermediate-sized production facilities and lower volume specialty products.

## KEY BENEFITS



Operational  
Efficiency

- Increased throughput with speeds up to 3.3 cycles per minute
- User friendly touch screen control panel stores factory settings and programmable settings
- The large vacuum chamber allows for the packing of a wide variety of different sized products



Product  
Integrity

- Uses CRYOVAC® brand oxygen barrier bags which provide superior oxygen barrier and sealant technology to help protect the product from contamination from the outside environment
- Has a hygienic design enabling convenient cleaning mode and fully 'washdown' capability
- Removes the oxygen from the package providing product integrity and longer shelf life



Brand  
Experience

- Provides superior product appearance with CRYOVAC® brand oxygen barrier bags reducing purge, preserving flavor and quality, and extending shelf life
- Produces packages with superior gloss and transparency which, when combined with two sided printed graphic capabilities, showcases the product and brand



## TECHNICAL DATA



### MACHINE DIMENSIONS

SEE MACHINE LAYOUT

MAX LENGTH: 170" (4305 mm)  
WIDTH: 50" (1260 mm)  
HEIGHT: 75" (1890 mm)

### PRODUCT DIMENSIONS

LENGTH/HEIGHT: 8.6"/29.3"  
(225 mm/745 mm) max.



### WEIGHT

WEIGHT: 7000 lbs (3200 kg) approx.



### SEALING BARS

LENGTH/HEIGHT: 59" / 1.2" (1500 mm/30 mm)  
1.2" / 2.5" (30 mm/65 mm) optional  
DISTANCE BETWEEN THE SEALING BARS: 30" (765 mm)



### NO. OF OPERATORS

1 or 2 operators



### SPEED

WORKING SPEED: 3 - 3.3 cycles/min (depending on product type and pumps used, with belt at maximum speed)



### UTILITIES

ELECTRICAL: 400 V (other voltages available on request)  
NO. PHASES: 3 + earth  
FREQUENCY: 50/60 Hz  
ENERGY CONSUMPTION PER HOUR: 1 kWh without vacuum booster pump  
4.2 kWh with vacuum booster pump  
AIR: 0.6 MPa (6 bar)  
CONSUMPTION: 15 Nm<sup>3</sup>/h



### BAG DETAILS

WIDTH: To suit product  
LENGTH: To suit product  
BAG TYPE(S): Current range of CRYOVAC® brand shrink bags (automatic feeding only with OSB™ bags)

## LINE LAYOUT EXAMPLE

