

Recycled Mailer/Parcel Film

Recycled mailer film is specifically engineered for ecommerce order fulfillment applications. The co-extruded film contains a unique blend of resins, plus at least 25% recycled content.

The white opaque, matte exterior finish provides security and is ideal for both direct thermal transfer imprinting and adhesive label applications.

USER BENEFITS

- At least 25% pre-consumer recycled content
- Recyclable anywhere plastic bags are accepted
- Superior strength and reinforced side seals

TYPICAL APPLICATIONS

- Soft Goods Fulfillment
- Pharmacy Fulfillment
- Industrial Fulfillment
- Novelty Fulfillment
- Catalog Order Fulfillment

TECHNICAL SPECIFICATIONS

Compliances: N/A

Press Printing: Yes with restrictions

Imprinting: Yes

Trim Seal: Yes

Mil Thickness: 2.0, 2.5, 3.0



Performance Data	U/M	2.0 mil	2.5 mil	3.0 mil	ASTM
Haze	%	Opaque	Opaque	Opaque	D-1003
Puncture Resistance (Dart)	grams	249	292	396	D-1709
Tensile Strength MD	psi	4246	4450	4930	D-882A
Tensile Strength TD	psi	4085	4315	4479	D-882A
Elongation MD	%	578	620	673	D-882A
Elongation TD	%	647	679	690	D-882A
Elmendorf Tear MD	grams	678	1063	1361	D-1922
Elmendorf Tear TD	grams	1360	1678	2100	D-1922
OTR	cc/100in ² /day	N/A	N/A	N/A	D-3985
MVTR	cc/100in ² /day	N/A	N/A	N/A	F-1249



Due to the recycled content of the material, the physical properties of this film are subject to vary beyond the typical expectations of virgin film. This data should be used for reference purposes only. Certain minimum purchase volumes may apply.