

Autobag®

BRAND AUTOMATED SYSTEMS

Translucent, UV Inhibiting Film - UV

BENEFITS

The Translucent UV Block Film is a polyethylene product with a UV block additive.

This material is supplied in clear as standard, other colour options are available, minimum order quantities may apply.

STORAGE

Store in a dry area, temperature should be between 10-30°C. Not to be stored in direct sunlight.



Recycle Ready*

OPTIONAL FEATURES

- Air Relief Hole
 - Full
 - Perforated
 - Butterfly
- Easy Open Perforation
 - Vertical
 - Horizontal
- Hanger Hole
 - Standard euroslot
 - Triangular euroslot
 - Hanger hole

*An addition of 3% UV additive to a 100µm film will screen out up to 90% of harmful UV radiation up to a wavelength of 340nm.

*Degree of recyclability will vary depending on scope and availability of flexible film collection, sortation and recycling programs.



TYPICAL APPLICATIONS



O' rings



Seals & gaskets



Rubber products

TECHNICAL SPECIFICATIONS

Compliance	ISO 9001:2015; ISO 14001:2015; BRC
Flexographic printing	Yes
In-line printing	Yes
Trim seal	Yes
Bag thickness	35, 50, 75 and 100 µm
System compatibility	Autobag; SidePouch

*with limitations



LDPE 4 Plastic